

HELIOS RADIANT IRK WIDE ANGLE

Cod. EHT1-20WA

Senza vetro termoresistente
e grande parabola per una maggiore
ed omogenea diffusione del calore

Without heat resistant glass
and wide reflector for more
widespread uniform heat.



Modello applicabile a parete e su
supporto mobile, dotato di parabola
con grado di angolazione molto ampio.
Senza vetro.
Struttura in acciaio verniciato.

Dotato di aggancio per fissaggio a
parete, cavo elettrico 3 m,
spina schuko pressofusa.

Altezza di installazione consigliata
per singolo apparecchio*:
2,50/3,00 m

Dimensioni cm 48x24x20
Imballo cm 57x28,5x22,5

Peso netto kg. 5,00
Peso lordo kg. 6,50


Revolving model for wall
instal- lation, equipped with
a very wide angle rate reflector.
Without glass.
Structure in bake painted steel.

Equipped with bracket for wall
installation, 3 m electric cable,
schuko plug.

Installation height recommended
for single heater*:
2,50/3,00 m

Dimensions cm 48x24x20
Packaging cm 57x28,5x22,5

Net weight kg. 5,00
Brut weight kg. 6,50



TEST TERMICO

Temperatura ambiente 8°C
Installazione riscaldatore 45°

A (altezza) = 2,5 m
B (profondità) = 3 m
C (larghezza) = 4 m

ZONA COMFORT
TEMPERATURA MEDIA
A PAVIMENTO 26,5°C

THERMIC TEST

Environment temperature 8°C
Heater Installation 45°

A (height) = 2,5 m
B (depth) = 3 m
C (length) = 4 m

COMFORT ZONE
MEDIUM TEMPERATURE
ON FLOOR 26,5°C



Cod.	Bar code	Colore	Potenza (Watt)	IP*	Cavo	Spina schuko	Installazione	Zona riscaldata (mq circa)
EHT1-20WA	105 856	Bicolore Bianco Ral 9016 e Ferro micaceo	2000	X5	3 m	x	A muro a 45°/ a soffitto	12/14

*per interni ed esterni
NON TEME PIOGGIA E SPRUZZI
D'ACQUA (brevetto Star Progetti)

Code	Bar code	Colours	Power (Watts)	IP*	Cable	Schuko plug	Installation	Heated area (sqm about)
EHT1-20WA	105 856	Bicolor White Ral 9016 and Cast iron	2000	X5	3 m	x	Wall 45°/ ceiling	12/14

*for indoors and outdoors
PROTECTED AGAINST RAIN AND WATER SPRAYS
(Star Progetti PATENT)



BULBI DI RICAMBIO / SPARE BULBS

Bulbo 2000 Watt (Cod. SP990527)
Bulb 2000 Watts (Code SP990527)

*SONO POSSIBILI QUOTE DI INSTALLAZIONE
PIÙ ELEVATE IN BASE AL PROGETTO
*HIGHER INSTALLATION QUOTAS ARE POSSIBLE
DEPENDING ON THE PROJECT